

INTRODUCTION

Movex **STPro100** is a high-performance self-adhesive butyl rubber tape incorporating non-woven polyester fleece, designed to be used as high strength reinforcement layer to resist various building movement in joints. It has very good bond to various substrates such as bricks, concrete, metal, wood & etc. The unique fleece allows many finishing materials to have excellent bond to the tape.

ADVANTAGES

- Fast installation, just peel and stick application.
- No torch-on or hot air needed for installation.
- Readily conforms to irregular surface profiles.
- Does not contain bitumen making it more environment friendly.
- Does not contain bentonite which is liable to dissolve in entrapped water.
- Excellent double bond to substrate and toppings.



PRODUCT DATA TESTED

Tensile Strength (longitudinal direction)	230 N/5 cm
Tensile Strength (transverse direction)	115 N/5cm
Elongation at Break (longitudinal direction)	69%
Elongation at Break (transverse direction)	60%
90° Peel Adhesion	11.1N//cm

Product were 1.00 thick when tested, excluding paper

USES

- To seal joint between floor slab and wall.
- Can be used for most substrates.
- Can receive tiling direct.

INSTALLATIONS

- Clean the surface using a brush and remove any dirt, debris or high points in the concrete.
- Remove the release paper from the adhesive and position **STPro 100**.
- Firmly press the entire surface of **STPro 100** into place using a roller or by hand to ensure proper bonding of the membrane.

PACKAGING & DIMENSION

- 1.0mm(thk) x 100mm(w) x 15metre(l)