

INTRODUCTION

SwellPro FTP is meant for pressure resistant and watertight sealing of hollow formwork spacers. SwellPro FTP is easy to install in one single movement (installation time = 1 second). No finishing or after-treatment is required.

ADVANTAGES

- Hard core guarantees pressure resistance up to 6 bar
- Soft sealing guarantees 100% waterproof up to 6 bar
- SwellPro FTP is fast and easy in use
- Installation in one single move (installation time = 1 second), use only a hammer
- Idiot-proof: wrong installation impossible thanks to smart sealing system
- No finishing or after-treatment required







100% waterproof to
6BAR

DESCRIPTION

- SwellPro FTP consists of an impact proof and pressure resistant core and a water swellable soft sealing.
- SwellPro FTP guarantees a pressure resistant and waterproof sealing of hollow spacers made of PVC, fibre cement or steel.

PRODUCT DETAILS

	Product Name	Colour	Quantity/Bag	Quantity/Box	Quantity/Pallet
	SwellPro FTP22	Red	100	1,000	18,000
	SwellPro FTP24	Red	100	500	9,000
	SwellPro FTP26	Red	100	500	9,000
	SwellPro FTP32	Red	100	500	9,000
	SwellPro FTP34	Red	100	500	9,000

Disclaimer: The information and the recommendations relating to the application and end use of this product are given in good faith and are based on the information provided by the manufacturer of the product and/or the Company's current knowledge and experience in connection with the product when properly stored, handled and applied under normal conditions and no liability of final function at the job site is assumed. In practice, the differences in materials, substrates and actual size conditions are such that no warranty in respect of merchantability or fitness for particular purpose, nor any liability by the Company will be accepted for misuse, misreading or derivation from recommended guidelines in respect of this product and the user shall determine the suitability of the product for his intended use and all risks and liability in connection therewith. The information contained in the brochure may change at any time without notice.

INSTALLATION

The SWELLPRO FTP fits in spacers with an inner diameter of 22, 24 or 26mm and can be customized to your specific formwork.

- 1) Position the Swellpro FTP in the formwork spacer
- 2) Hammer the Swellpro FTP into the formwork spacer
- 3) No additional finishing or after-treatment required



The water swellable sealing products by Movex are based on the unique Active Sealing Technology. Our products expand on contact with water. This is how they create an active seal to combat moisture infiltration. The Movex products are self-correcting and thus also sealing the unevenness and imperfections of the concrete.