

DESCRIPTION

MVX SealPro is a one part, moisture curing, elastic joint sealant based on polyurethane. It has excellent durability as low-modulus, high-elongation.

CHARACTERISTICS

- Excellent resistance of building movement due to vary temperature
- Eco-friendly (phthalates contents free)
- One-component, ready for use
- Good adhesion to many substrates
- It has wide temperature range (-20°C~70°C) that can used
- Moisture curing
- Fast curing
- Excellent workability, easy to use
- Can be overpainted
- Weather resistance, excellent aging resistance



PACKAGING

- Packaging: Sausage (600ml)

APPLICATION

- Do not open containers until ready to use
- Remove the dust, oil and other contaminants from the surface
- Filling of construction joints, expansion wall joints and civil engineering field
- Repair of concrete cracks and sealing of around ALC and metal sashes
- Sealing of window perimeter, siding, doors
- Horizontal and vertical joints
- Window frames and doors
- Interior and exterior
- Adheres to substrates such as concrete, masonry, aluminum, wood and stucco

STORAGE

9 months from production date if stored properly in undamaged and unopened original sealed packaging in cool dry conditions. Protect from direct sunlight and frost.

WARNING

- Avoid prolonged contact with skin and eyes
- For the porous surface, ALC, other concrete and urethane foam, it may give air bubbles on the surface and inside one should test before application. In case of air bubbles detected, one need to apply the concrete primer prior to the sealant applications
- It may give color change painting over this sealant, so need to test before full applications
- In case of skin contact, wipe with clean dry cloth and wash thoroughly with water and mild detergent
- In case of eye contact, flush immediately with copious amounts of water and contact medical doctor
- Do not take internally
- Keep out of the reach of children
- Avoid heat, fire, direct sunlight
- Do not use over 50°C and allow it to freeze
- Store unused sealant in dry area at less than 25°C
- For additional information, please refer to MSDS or contact us

TEST DATA

Analysis Items	Unit	MVX SealPro
Cure System	-	Moisture curing
The time of surface hardening	At 23°C	30-40 min
Density	g/m3	1.45±0.05
Processing Temperature	°c	+5~35
Curing Rate	mm/24hr	2~2.5
Shore A hardness	-	35±5
Tensile Modulus	Mpa	1.8~2.5
Elongation	%	700~800
Shelf Life	Month	9
Color	-	White, Grey etc
Elastic recovery	%	91%≤

Disclaimer. The information and recommendations relating to the application and end use of this product are given in good faith and are based on the information provided by the manufacturer of the product and/or the Company's current knowledge and experience in connection with the product when properly stored, handled and applied under normal conditions and no liability of final function at the job site is assumed. In practice, the differences in materials, substrates and actual size conditions are such that no warranty in respect of merchantability or fitness for particular purpose, nor any liability by the Company will be accepted for misuse, misreading or derivation from recommended guidelines in respect of this product and the user shall determine the suitability of the product for his intended use and all risks and liability in connection therewith. The information contained in the brochure may change at any time without notice.